






WARNING!

SECTIONS  OF THE ASSEMBLY MARKED  ARE NOT SHIELDED AND MUST BE SHIELDED BY AN INTERACTIVE GUARDING SYSTEM. BONDIOLI & PAVESI DECLINES RESPONSIBILITY IF PROPER GUARDS ARE NOT PROVIDED OR MAINTAINED.

1 3/4" Z=6

| | | | | | | | |
|---|--|---|--|---|-------------------------|--------------------------------------|---------------|
| 1 | CODICE CODE | LATO TRATTORE TRACTOR SIDE | LATO MACCHINA IMPLEMENT SIDE | TIPO-TYPE | CLIENTE / CUSTOMER | RIF. CLIENTE / CUSTOMER REF. | |
| 2 | 6WL265909R LR24 2500 Nm |  |  | SFT-S8 | 3600522 SAMSON AGRO A/S | 935000319 | |
| 3 | | | | DATA / DATE | DISEGNATO / DESIGNED BY | TIPO DI MACCHINA / TYPE OF IMPLEMENT | |
| | | | | 2/2/09 | R. Moretti | | |
| | | | | LUNGHEZZA MAX IN LAVORO MAX WORKING LENGTH | STUDIO / DESIGN | ORIGINE / ORIGIN | |
| | | | | | TRS8R111005 | | |
| 4 |  RILSAN L=960 | VELOCITA' MAX MAX SPEED | M max | LUNGHEZZA MAX TEMPORANEA MAX TEMPORARY LENGTH | NOTE / NOTES | | CODICE / CODE |
| | | 540 min ⁻¹ | | LUNGHEZZA MAX NON IN ROTAZIONE MAX LENGTH AT STANDSTILL | SPECIALE PER: POS.2; | | REV. |
| | | | | | | DS8R111CEIK01 | |