



6.7	971000032	O-Ring DOWTY 032 (1,78x47,35)	1
6.6	971000812	O-Ring DOWTY 812 (2,62x20,63)	1
6.5	977050034	Guarniz.pist.50/34 H.18,40	1
6.4	972000224	Anello Antiestr. DOWTY 224	1
6.3	971000224	O-Ring DOWTY 224 (3,53x44,04)	1
6.2	976250330	Guarniz.stelo 25/33/6,5	1
6.1	975000025	Raschiatore D. 25	1
6	35105025	Guarnizioni Cilindro 50/25	1
5	981201500	Dado Autob.BassoM20x1,5 DIN985	1
4	31050200	Pistone D.50 F.20 H.37	1
3	32050250	Testa 50/25 H.46	1
2	DK2774P2	Stelo Cilindro 50/25x360	1
1	DK2774P1	Canna cilindro 50/25x360	1
POS	CODICE	DESCRIZIONE	QTÀ

CUSTOMER APPROVAL		Painting: BLACK RAL 9005	Weight
APPROVED BY	APPROVAL DATE	Cylinder Marked FA MONTH/YEAR	6 kg
Max Working Pressure 220 Bar. Working temperature from -20C to +80C Max working speed 0,5 m/s			
N°	DATE	MODIFICATION	Approved by
FAROIL hydraulic cylinders		DANITECH	CODE N°
TOLERANCE REF: DOC-A087		Cylinder	INDEX
DOC-A116 Rev.C		50/25x360	SCALE
CUSTOMER REF.		DK2774	DATE
			DESIGNED BY
			APPROVED BY
			P.D.
			E.B.