



Finitura superficiale (Painting): BLACK PAINTED RAL9005 (NERO RAL9005) Weight 8 kg

Pressione di esercizio (Working Pressure): 220 Bar Pressione di prova (Testing Pressure): 180 Bar

Temperatura di lavoro (Working temperature) da (from) -20 C a (to) +100 C Velocità di lavoro (Max working speed) 0,5 m/s

8.7	971000035	O-Ring DOWTY 035 (1,78x56,87)	1
8.4	972000227	BACK UP RING DOWTY 227	1
8.3	971000227	O-Ring DOWTY 227 (3,53x53,57)	1
8.2	976300380	ROD SEAL 30/38/6,5 TTS/L 579	1
8.1	975000030	WIPER D. 30 PW-GHK 311	1
8.5	977060044	PISTON SEAL 60/44 H.18,40 TPM9020	1
8.6	971000123	O-Ring DOWTY 123 (2,62x29,82)	1
8	351860302	Sealing kit 60/30 32060300+31460270	1
POS.	CODICE	DESCRIPTION	QTÀ

B 03/03/2015		Added adjustable end; Was Ø25,25		Giroladini	
A 30/01/2015		Era Piatto Pantografato 941052525		Donegà	
N°	DATE	MODIFICATION	Approved by	N°	DATE
DESCRIPTION			AP GYLLE		
DESCRIPTION			CYLINDER		
TOLERANCE REF: DOC-A087			60/30x300		
CUSTOMER REF.			6517		
DOC-A116 Rev.C		CODE N°		INDEX	
		DK3158		B	
		SCALE		////	
		DATE		03/03/2015	
		DESIGNED BY		M.M.	
		APPROVED BY		E.B.	