


TCN(S) - OIL FILL PLUG

TSN - OIL DRAIN PLUG



Threaded hex head oil plug ensuring high mechanical resistance at both low and high temperature, dimensional stability and shock resistance. TCN and TCNS style have the “fill” graphic symbol and the word OIL moulded on the top. TSN has a graphic symbol of drain moulded on the top.

-**Breather:** model TCNS has a breather hole located on the side of the hex with a diameter from 2 to 3,5 mm, depending on the size.

-**Material:** Polyamide PA66.

-**Sealing:** flat fiber gasket.

-**Maximum working temperature:** 100°C/212°F.

Special versions

-**Sealing:** flat gasket NBR 70 Shore.

-**Color:** red.

	Cod.		F	CH	D	h2	h1	Nm	Pack.
TCN/14	TCNS/14	TSN/14	G 1/4"	17	19,5	9	7	5	100
TCN/38	TCNS/38	TSN/38	G 3/8"	18	22	10	7,5	8	100
TCN/12	TCNS/12	TSN/12	G 1/2"	23	28	11	7,5	9	100
TCN/34	TCNS/34	TSN/34	G 3/4"	30	34	11	9	11	50
TCN/1	TCNS/1	TSN/1	G 1"	36	42	12	10,5	20	50
TCN/114	TCNS/114	TSN/114	G 1 1/4"	42	51	13,5	12	-	25
TCN/112	TCNS/112	TSN/112	G 1 1/2"	50	58	16	10	-	25
TCN/2	TCNS/2	TSN/2	G 2"	64	74	16	12	-	25
TCN/10.15*	TCNS/10.15*		M 10x1,5	18	22	9	7	5	100
TCN/12.15*	TCNS/12.15*		M 12x1,5	18	22	9	7	5	100
TCN/14.15	TCNS/14.15	TSN/14.15	M 14x1,5	17	19,5	8	7	5	100
TCN/16.15	TCNS/16.15	TSN/16.15	M 16x1,5	18	21	10	7,5	6	100
TCN/18.15	TCNS/18.15	TSN/18.15	M 18x1,5	21	26	10	7,5	7	100
TCN/20.15	TCNS/20.15	TSN/20.15	M 20x1,5	24	28	10	8	8	100
TCN/22.15	TCNS/22.15	TSN/22.15	M 22x1,5	24	28	11	8	10	100
TCN/40.15	TCNS/40.15	TSN/40.15	M 40x1,5	42	52	13	10		25

*Hex surface blank and rubber flat seal.