




ZEC S.p.A.
Via Lungolorno 11 - 42052 Colorno (PR) - Italia
Tel. 0521 816631 - Fax 0521 816772
info@zecspa.com - www.zecspa.com

Capitale sociale: Euro 1.000.000
C.F., P.IVA e n. Iscr. Reg. Imprese Parma: IT01720400348
Numero REA: PR - 173914

OL7 Series thermoplastic hose - Oil proof Cover*

- PRESSURE FROM 70 TO 250 BAR
- SAE 100R7, ISO 3949 STANDARDS
- LLOYD'S REGISTER TYPE APPROVAL
- CREATED FOR MEDIUM PRESSURE HYDRAULIC USE



TECHNICAL FEATURES

Metric

Code	ID			OD	1:4 WP	R MIN	g	Ferrule Code
	inch	mm	DN					
OL710100	1/8"	3.5	3	8.5	230	12	57	BP18R7
OL78940100	5/32"	4.0	4	8.9	250	25	58	BP532R7
**OL720100	3/16"	4.8	5	10.0	210	30	73	BP316R7
**OL730100	1/4"	6.4	6	11.8	200	35	90	BP14R7
**OL740100	5/16"	8.0	8	14.3	190	45	128	BP516R7V
**OL750100	3/8"	9.7	10	16.0	175	55	155	BP38R7V
**OL760100	1/2"	13.0	12	20.3	140	75	219	BP12R7V
**OL770100	5/8"	16.0	16	23.5	105	120	277	BP58R7V
**OL780100	3/4"	19.2	19	26.5	90	145	330	BP34R7V
**OL790100	1"	25.6	25	33.6	70	200	403	BP1R7V

TECHNICAL FEATURES

Technical-constructive features:

Inner core in thermoplastic polyester, polyester textile reinforcement and exterior covering in antiabrasion polyurethane, stabilized against UV rays and microorganisms-resistant, micro perforated for the conduction of air and compatible gases.

Applications:

Hoses of the OL7 Series have been created for medium pressure hydraulic use.

Working temperature:

from -40°C to +100°C from -40°F to +212°F. Max. working temperature of air, water and water-based fluids is + 70°C (+158°F).

Working pressure:

Safety ratio 1:4

Vacuum rating:


0.93 bar; 700 mm Hg

Specifications:

Hoses meet or exceed SAE J517 sect. SAE 100R7 – and ISO 3949 Standards.

** Lloyd's Register TYPE APPROVAL Hoses.

*The oil-proof feature of the cover means that the hose is resistant to prolonged contact with oils and lubricants.

OPTIONAL Color Multi-tube Long Length Cover Packing**NORMATIVE**

ISO 3949
LLOYD'S REGISTER TA
SAE J517-100 R7

For any further information about the optional items, please contact the sales office (sales@zecspa.com)