









WARNING!

SECTIONS  OF THE ASSEMBLY MARKED ARE NOT SHIELDED AND MUST BE SHIELDED BY AN INTERACTIVE GUARDING SYSTEM. BONDIOLO & PAVESI DECLINES RESPONSIBILITY IF PROPER GUARDS ARE NOT PROVIDED OR MAINTAINED.

WARNING!
 Assembly supplied without end yoke, torque limiter or clutch. Customer must follow Bondioli & Pavesi recommendations for installation.

PERICOLO!
 Trasmissione fornita senza forcella di estremità, o dispositivo di sicurezza. Il cliente deve seguire le raccomandazioni Bondioli & Pavesi per l'installazione.

PROTEGGERE I PERNI CON I TAPPI E FORNIRE I 2 CUSCINETTI E I 2 SEEGER A PARTE

| | | | | | | | |
|---|--|---|---|---|---|--------------------------------------|---|
| 1 | CODICE CODE WR9 | LATO TRATTORE TRACTOR SIDE | LATO MACCHINA IMPLEMENT SIDE | TIPO-TYPE SFT-SH | CLIENTE / CUSTOMER 3600502 Dani-Tech A/S | RIF. CLIENTE / CUSTOMER REF. | |
| 2 | CODICE CODE 000 |  |  | DATA / DATE 1/4/2015 | DISEGNATO / DESIGNED BY A.Caffagni | TIPO DI MACCHINA / TYPE OF IMPLEMENT | |
| 3 |  L=1015 |  |  | LUNGHEZZA MAX IN LAVORO MAX WORKING LENGTH Lw=1699 | STUDIO / DESIGN | ORIGINE / ORIGIN |  |
| 4 |  RILSAN L=1025 | VELOCITA' MAX MAX SPEED 540 min ⁻¹ | M max 6750 Nm | LUNGHEZZA MAX TEMPORANEA MAX TEMPORARY LENGTH Lt=1862 | NOTE / NOTES SPECIALE PER MANCANZA ATTACCO | | |
| | | | | LUNGHEZZA MAX NON IN ROTAZIONE MAX LENGTH AT STANDSTILL Ls=1943 | | | REV. 0 |